



## D-10CX

### Two Post Lift

The D-10CX is a 10,000 pound two post lift that has a proven design and produces real results in virtually any type of service scenario. This vehicle lift is designed to be the workhorse of any automotive repair business and will be an asset to any repair facility it is installed in. This two post lift will give you years of trouble free service at an affordable cost. Each component of the lift was engineered better, stronger, and more economical to pass the savings to you.

The D-10CX is making its way into the premiere commercial two post lift and has become a favorite among shop owners. With an overall width of 145" this auto lift will fit perfectly into most repair bays. See below for all the exciting features this lift has to offer.



#### FEATURES

- \* Dannmar Two Post Vehicle Lifts 10,000 lbs lifting capacity
- \* Single point safety release on simple to use controls
- \* Space saving design works perfectly in almost any sized repair bay
- \* Dual-Synchro equalization system maintains equal lifting
- \* Maintenance-free, "Dura-Glide" polyethylene load bearings
- \* Single-piece columns for added strength and less fatigue
- \* Dual hydraulic cylinders combined with "direct-drive" lifting system provides 2-to-1 lifting speed and rugged dependability
- \* Heavy-duty lift arms feature automatic safety restraints
- \* Comes standard with eight piece truck and van adapter set
- \* Includes detailed installation and maintenance instructions, graphic safety and maintenance decals, and a vehicle lifting point guide and safety instruction placard guidelines.
- \* Oversize column base plates provide strong support
- \* Safety locks in each column spaced every three inches
- \* Heavy-duty 3/8" equalizer cables
- \* Convenient storage is included for truck and van adapters

#### SPECIFICATIONS

- \* **Lifting Capacity:** 10,000 lbs. / 4546 kg.
- \* **Style:** Clear Floor
- \* **Overall Height:** 145" / 3683 mm.
- \* **Overall Width (Outside of Base plates):** 145" / 3683 mm.
- \* **Overall Width (Outside of Columns):** 137" / 3480 mm.
- \* **Width Between Columns:** 115" / 2921 mm.
- \* **Minimum Reach (Front Arm):** 28" / 711 mm.
- \* **Maximum Reach (Front Arm):** 42" / 1068 mm.
- \* **Minimum Reach (Rear Arm):** 42" / 1068 mm.
- \* **Maximum Reach (Rear Arm):** 61" / 1549 mm.
- \* **Minimum Pad Height:** 4" / 102 mm.
- \* **Rise:** 73" / 1854 mm.
- \* **Maximum Lifting Height (Pad Only):** 73" / 1854 mm.
- \* **Maximum Lifting Height (Pad & 6" Adapter):** 79" / 2007 mm.
- \* **Drive Thru Clearance:** 90" / 2286 mm.
- \* **Lifting Time:** 45 seconds
- \* **Maximum Load Per Arm:** 2,250 lbs. / 1023 kg.
- \* **Motor:** 220 VAC 60Hz. 1Ph



Telephone: 877-4-R LIFTS - (877-475-4387) - Fax: 877-261-5594 - Or Email Us At: [info@portagelift.com](mailto:info@portagelift.com)

\*Please note that these specifications are subject to change without notice. It is best to confirm these specifications with a sales representative at the time of purchase.