



D-7X

Four Post Lift



Dannmar Four Post Vehicle Lifts Extended 7,000 lbs lifting capacity Designed to work with a wider variety of vehicles, the D-7X four post lift is a longer, wider and taller version of the standard D-7. Having that extra room can make all the difference for a car collector or someone needing more parking spaces. The D-7X four post lift is perfect for that exact application. It features a single point safety handle and a very durable hydraulic pump assembly.

If you have the room in your garage or shop, purchase the D-7X four post lift. It will give a wider range of flexibility with cars and trucks.

FEATURES

- Dannmar D-7X four post lift is extra wide and long
- Simple controls make for an easier operation
- Spring loaded safety locks are located on each column
- Self-lubricating UHMW polyethylene internal slide blocks are also located in each column
- Features a single safety lock release handle
- Bulky single hydraulic cylinder is located underneath runway for added room
- Reliable electric/hydraulic power unit assembly
- The drive-up ramps are detachable when needed
- Designed to be free standing
- Self-lubricating bearings and cable sleeves
- Runways include rail-kit as an optional accessory

OPTIONS

- Caster Kit
- Jack Platform
- Plastic Drip trays
- Aluminum (Lightweight) Drive Up Ramps
- Steel Deck (Fills the Center of the lift)
- Aluminum Deck (Fills the Center of the lift)
- Cycle Vise (Motorcycle Adaptor attaches to Runway)

SPECIFICATIONS

- **Lifting Capacity:** 7,000 lbs. / 3182 kg.
- **Overall Width:** 117" / 2972 mm.
- **Outside Length:** 194-1/2" / 4940 mm.
- **Overall Length:** 227-1/2" / 5779 mm.
- **Height Columns:** 94" / 2388 mm.
- **Minimum Runway Height:** 4-1/2" / 114 mm.
- **Maximum Rise:** 85" / 2159 mm.
- **Maximum Lifting Height:** 89" / 2261 mm.
- **Width Between Columns:** 103" / 2616 mm.
- **Runway Width:** 18-1/2" / 470 mm.
- **Width Between Runways:** 37-1/2" / 953 mm.
- **Length of Runways:** 185" / 4699 mm.
- **Locking Positions:** 13
- **Clearance At Each Locking Position:** 1. 17" 2. 32.5" 3. 37" 4. 41.5" 5. 46" 6. 50.5" 7. 55" 8. 59.5" 9. 64" 10. 68.5" 11. 73" 12. 77.5" 13. 82"
- **Lock Spacing:** Every 4-1/2"
- **Lifting Time:** 45 Seconds
- **Standard Motor:** 110 VAC 60Hz. 1Ph



PORTAGE LIFTS
TELEPHONE: 877-4-R LIFTS
(877-475-4387)
FAX: 877-261-5594

OR EMAIL US AT:
INFO@PORTAGELIFT.COM