



## D9-2

### Two Post Lift



The D9-2 is the perfect example of the Dannmar product model. This floorplate vehicle lift model offers some serious benefits that make it very desirable to both the service technician and the business owner.

This model of vehicle lift is all about versatility. Generally used in situations where there is ceiling height issues this auto lift excels, but place it in a space with no height restrictions, and feel free to lift vans, trucks, and other high profile vehicles at will. In addition with the D9-2 arms raised to their full height it gives a healthy 6 feet of clearance for service technicians to get under the vehicle and get the job done. If you're looking for a little more room between the two posts, check out the extra-wide D9-2X model.

#### FEATURES

- \* Dannmar Two Post Vehicle Lifts 9,000 lbs lifting capacity
- \* Low column height accommodates low-ceiling installations
- \* Maximum lifting height provides 6 feet of under-car clearance
- \* Able to raise high profile vehicles with no restrictions
- \* Maintenance-free, "Dura-Glide" polyethylene load bearings
- \* Single-piece columns for added strength and less fatigue
- \* Dual hydraulic cylinders combined with "chain over" lifting system provides 2-to-1 lifting speed and rugged dependability
- \* Dual-Synchro equalization system maintains equal lifting
- \* Heavy-duty lift arms feature automatic safety restraints
- \* Comes standard with eight piece truck and van adapter set
- \* A low-profile bottom cover plate means easier vehicle positioning
- \* Includes detailed installation and maintenance instructions, graphic safety and maintenance decals, and a vehicle lifting point guide and safety instruction placard guidelines
- \* Oversize column base plates provide strong support
- \* Safety locks in each column spaced every three inches
- \* Heavy-duty 3/8" and 1/2" equalizer cables
- \* Convenient storage is included for truck and van adapters

#### SPECIFICATIONS

- \* **Lifting Capacity:** 9,000 lbs. / 4091 kg.
- \* **Overall Height:** 113" / 2870 mm.
- \* **Overall Width (Outside of Base plates):** 132" / 3353 mm.
- \* **Overall Width (Outside of Columns):** 124" / 3150 mm.
- \* **Floorplate Height:** 2" / 51 mm.
- \* **Width Between Columns:** 105" / 2667 mm.
- \* **Minimum Reach (Front Arm):** 32" / 813 mm.
- \* **Maximum Reach (Front Arm):** 47" / 1194 mm.
- \* **Minimum Reach (Rear Arm):** 35" / 889 mm.
- \* **Maximum Reach (Rear Arm):** 52" / 1321 mm.
- \* **Minimum Pad Height:** 4" / 102 mm.
- \* **Rise:** 74" / 1880 mm.
- \* **Maximum Lifting Height (Pad Only):** 76" / 1930 mm.
- \* **Maximum Lifting Height (Pad & 6" Adapter):** 82" / 2083 mm.
- \* **Drive Thru Clearance:** 96" / 2438 mm.
- \* **Lifting Time:** 45 seconds
- \* **Maximum Load Per Arm:** 2,250 lbs. / 1023 kg.
- \* **Motor:** 220 VAC 60Hz. 1Ph

